



CONFIDENTIAL & PROPRIETARY INFORMATION

This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM



NOTES:

- MAGNET PROPERTIES PER N-35SH:
 Br: 11,800-12,200 G
 Hc: 10,800-11,500 Oe
 Hci: ≥20,000 Oe
 T max: 150 C

2. SUPPLIED MAGNETIZED ACROSS THE DIAMETER

3. PARTS ARE BLACK EPOXY COATED



REV	DESCRIPTION	DATE	BY
B	Changed CAD, incl cert, 3D	1/30/14	BT

TOLERANCES
(UNLESS OTHERWISE NOTED)

DECIMAL METRIC
 X.XX = ± .01 X.X = ± .25
 X.XXX = ± .005 X.XX = ± .13

ANGLES
 ± .5°

DO NOT SCALE DRAWING

Alliance LLC		
1450 CLARK DRIVE, VALPARAISO, INDIANA 46385		
DESCRIPTION: 6.0 mm x 2.5 mm DISC MAGNET		
AMS P/N: AS5000-MD6SH		P/N: 072508AMS
GRADE: N-35SH	Drwg by: BT	REV LEVEL: B
COATING: EPOXY	Appr by: DV	Appr. Dated: 05-15-2013