



CONFIDENTIAL & PROPRIETARY INFORMATION

This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM



NOTES:

- MAGNET PROPERTIES PER N-42SH:
 Br: 12,900-13,200 G
 Hc: 11,900-12,600 Oe
 Hci: ≥20,000 Oe
 T max: 150 C
- SUPPLIED MAGNETIZED ACROSS THE DIAMETER
- PARTS ARE NICKEL PLATED FOR 15hrs SALT SPRAY MIN



| REV | DESCRIPTION | DATE | BY |
|-----|----------------------------|---------|----|
| B | Changed CAD, incl cert, 3D | 2/11/14 | BT |
| | | | |
| | | | |
| | | | |

| | |
|--|--------------|
| TOLERANCES (UNLESS OTHERWISE NOTED) | |
| DECIMAL | METRIC |
| X.XX = ± .01 | X.X = ± .25 |
| X.XXX = ± .005 | X.XX = ± .13 |
| ANGLES ± .5° | |
| DO NOT SCALE DRAWING | |

| | | |
|--|-------------|-------------------------|
| Alliance LLC 1450 CLARK DRIVE, VALPARAISO, INDIANA 46385 | | |
| DESCRIPTION: 8.0 mm x 3.0 mm DISC MAGNET | | |
| SENSOR MAGNET | | P/N: ALC8302 |
| GRADE: N-42SH | Drwg by: BT | REV LEVEL: B |
| COATING: Nickel | Appr by: DV | Appr. Dated: 08-18-2013 |