



CONFIDENTIAL & PROPRIETARY INFORMATION

This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM



NOTES:

- MAGNET PROPERTIES PER N-50:
 Br: 14,100-14,500 G
 Hc: 10,500-11,100 Oe
 Hci: ≥12,000 Oe
 Tmax: 80 C
- SUPPLIED MAGNETIZED THROUGH THE DIAMETER
- PARTS ARE NICKEL PLATED FOR 15hrs SALT SPRAY MIN.



REV	DESCRIPTION	DATE	BY
B	Changed CAD, incl cert, 3D	2/15/18	BT

TOLERANCES (UNLESS OTHERWISE NOTED)	
DECIMAL	METRIC
X.XX = ± .01	X.X = ± .25
X.XXX = ± .005	X.XX = ± .13
ANGLES ± .5°	
DO NOT SCALE DRAWING	

Alliance LLC		
1450 CLARK DRIVE, VALPARAISO, INDIANA 46385		
DESCRIPTION: 3.0 mm x 0.8 mm DISC MAGNET		
SENSOR MAGNET		P/N: ALC3008
GRADE: N-50	Drwg by: BT	REV LEVEL: B
COATING: Nickel	Appr by: DV	Appr. Dated: 05-27-2017