



CONFIDENTIAL & PROPRIETARY INFORMATION

This document contains Confidential and Proprietary Information of Alliance LLC, and all design, manufacturing, reproduction, use, and sale rights of such information are expressly reserved

ALL DIMENSIONS ARE IN MM



NOTES:

- MAGNET PROPERTIES PER N-40SH:
 Br: 12,600-12,900 G
 Hc: 11,500-12,200 Oe
 Hci: ≥20,000 Oe
 Tmax: 150 C
- SUPPLIED MAGNETIZED THROUGH THE THICKNESS
- PARTS ARE EPOXY COATED FOR 15hrs SALT SPRAY MIN.



REV	DESCRIPTION	DATE	BY
B	Changed CAD, incl cert, 3D	1/30/14	BT

TOLERANCES
(UNLESS OTHERWISE NOTED)

DECIMAL METRIC
 X.XX = ± .01 X.X = ± .25
 X.XXX = ± .005 X.XX = ± .13

ANGLES
 ± .5°

DO NOT SCALE DRAWING

Alliance LLC		
1450 CLARK DRIVE, VALPARAISO, INDIANA 46385		
DESCRIPTION: 3.5 mm x 0.75 mm DISC MAGNET		
SENSOR MAGNET		P/N: ALC3575
GRADE: N-40SH	Drwg by: BT	REV LEVEL: B
COATING: Epoxy	Appr by: DV	Appr. Dated: 05-15-2013